

户内 单相 环氧树脂浇注式

INTDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

○产品性能符合标准：DL/T 653-2009《电压并联电容器用放电线圈订货技术条件》

The voltage transformers are in accordance DL/T653-2009《Specification of discharge coils for high voltage parallel connection capacitor for order standards》;

○额定频率：50Hz 或 60Hz

Rated frequency 50Hz or 60Hz

○负荷功率因数：COS=Φ0.8(滞后)

Load power factor: COS=Φ0.8(lagging)

○污秽等级：IV 级

Pollution class: IV

○其他技术参数见下表

Other technical data see following table:



型号 Type	额定电压比 (kV) Rated voltage Ratio	准确级及准确组合额定二次输出 (VA) Accuracy class and accuracy class combination rated secondary output	放电量 (Mvar) (Mvar)	额定绝缘水平 (kV) Rated Insulating level
FDGE17/38.5(40,42,43.5,45)/√3-6.8-1W	38.5/√3/0.1/√3/0.1/3	0.2---20 0.5---50 1---100 6P-50	6.8	40.5/95/200
FDGE17/38.5(40,42,43.5,45)/√3-8.0-1W	40/√3/0.1/√3/0.1/3		8.0	
FDGE17/38.5(40,42,43.5,45)/√3-10.0-1W	42/√3/0.1/√3/0.1/3		10.0	
FDGE17/38.5(40,42,43.5,45)/√3-12.0-1W	43.5/√3/0.1/√3/0.1/3		12.0	

外形及安装尺寸 Overall dimension drawing

